



Week 8: *Midterm Review*

III EMSE 4571: Intro to Programming for Analytics

👤 John Paul Helveston

📅 February 28, 2022

Things to review

- Lecture slides, especially practice puzzles covered in class)
- Previous quizzes
- Memorize syntax for:
 - if / else statements
 - loops
 - functions
 - test functions

Basics

Operators: Relational (`=, <, >, <=, >=`) and Logical (`&, |, !`)

```
x <- FALSE  
y <- FALSE  
z <- TRUE
```

a Write a logical statement that compares the objects `x`, `y`, and `z` and returns `TRUE`

b) Fill in **relational** operators to make this statement return `TRUE`:

`! (x __ y) & ! (z __ y)`

c) Fill in **logical** operators to make this statement return `FALSE`:

`! (x __ y) | (z __ y)`

Numeric Data

Doubles:

```
typeof(3.14)
```

```
#> [1] "double"
```

"Integers":

```
typeof(3)
```

```
#> [1] "double"
```

Actual Integers

Check if a number is an "integer":

```
n <- 3  
is.integer(n) # Doesn't work!
```

```
#> [1] FALSE
```

```
n == as.integer(n) # Compare n to a  
converted version of itself
```

```
#> [1] TRUE
```

Logical Data

TRUE or FALSE

```
x <- 1  
y <- 2
```

```
x > y # Is x greater than y?
```

```
#> [1] FALSE
```

```
x == y
```

```
#> [1] FALSE
```

Tricky data type stuff

Logicals become numbers when doing math

```
TRUE + 1 # TRUE becomes 1
```

```
#> [1] 2
```

```
FALSE + 1 # FALSE becomes 0
```

```
#> [1] 1
```

Be careful of accidental strings

```
typeof("3.14")
```

```
#> [1] "character"
```

```
typeof("TRUE")
```

```
#> [1] "character"
```

Integer division: $\%/\%$

Integer division drops the remainder

```
4 / 3 # Regular division
```

```
#> [1] 1.333333
```

```
4 %/% 3 # Integer division
```

```
#> [1] 1
```

Integer division: $\%/\%$

Integer division drops the remainder

What will this return?

```
4 %/% 4
```

```
#> [1] 1
```

What will this return?

```
4 %/% 5
```

```
#> [1] 0
```

Modulus operator: `%%`

Modulus returns the remainder *after* doing integer division

```
5 %% 3
```

```
#> [1] 2
```

```
3.1415 %% 3
```

```
#> [1] 0.1415
```

Modulus operator: `%%`

Modulus returns the remainder *after* doing integer division

What will this return?

```
4 %% 4
```

```
#> [1] 0
```

What will this return?

```
4 %% 5
```

```
#> [1] 4
```

Number "chopping" with 10s (only works with $n > 0$)

The mod operator (`%%`) "chops" a number and returns everything to the *right*

```
123456 %% 1
```

```
#> [1] 0
```

```
123456 %% 10
```

```
#> [1] 6
```

```
123456 %% 100
```

```
#> [1] 56
```

Integer division (`%/%`) "chops" a number and returns everything to the *left*

```
123456 %/% 1
```

```
#> [1] 123456
```

```
123456 %/% 10
```

```
#> [1] 12345
```

```
123456 %/% 100
```

```
#> [1] 1234
```

Functions

Basic function syntax

```
functionName <- function(arguments) {  
  # Do stuff here  
  return(something)  
}
```

Basic function syntax

In English:

"**functionName** is a **function** of **arguments** that does..."

```
functionName <- function(arguments) {  
  # Do stuff here  
  return(something)  
}
```

Basic function syntax

Example:

"squareRoot is a **function** of **n** that...returns the square root of **n**"

```
squareRoot <- function(n) {  
  return(n0.5)  
}
```

```
squareRoot(64)
```

```
#> [1] 8
```

Test function "syntax"

Function:

```
functionName <- function(arguments) {  
  # Do stuff here  
  return(something)  
}
```

Test function:

```
test_functionName <- function() {  
  cat("Testing functionName()...")  
  # Put test cases here  
  cat("Passed!\n")  
}
```

Writing test cases with `stopifnot()`

`stopifnot()` stops the function if whatever is inside the `()` is not `TRUE`.

Function:

```
isEven <- function(n) {  
  return((n %% 2) == 0)  
}
```

- `isEven(1)` should be `FALSE`
- `isEven(2)` should be `TRUE`
- `isEven(-7)` should be `FALSE`

Test function:

```
test_isEven <- function() {  
  cat("Testing isEven()...")  
  stopifnot(isEven(1) == FALSE)  
  stopifnot(isEven(2) == TRUE)  
  stopifnot(isEven(-7) == FALSE)  
  cat("Passed!\n")  
}
```

When testing *numbers*, use `almostEqual()`

Rounding errors can cause headaches:

```
x <- 0.1 + 0.2  
x
```

```
#> [1] 0.3
```

```
x == 0.3
```

```
#> [1] FALSE
```

```
print(x, digits = 20)
```

```
#> [1] 0.300000000000004441
```

Define a function that checks if two values are *almost* the same:

```
almostEqual <- function(n1, n2, threshold  
= 0.00001) {  
  return(abs(n1 - n2) <= threshold)  
}
```

```
x <- 0.1 + 0.2  
almostEqual(x, 0.3)
```

```
#> [1] TRUE
```

Make sure you know how to write `almostEqual()`

```
almostEqual <- function(n1, n2, threshold = 0.00001) {  
  return(abs(n1 - n2) <= threshold)  
}
```

Conditionals

Use `if` statements to filter function inputs

Example: Write the function `isEvenNumber(n)` that returns `TRUE` if `n` is an even number and `FALSE` otherwise. **If `n` is not a number, the function should return `FALSE`.**

```
isEvenNumber <- function(n) {  
  return((n %% 2) == 0)  
}
```

```
isEvenNumber(2)
```

```
#> [1] TRUE
```

```
isEvenNumber("not_a_number")
```

```
#> Error in n%%2: non-numeric  
argument to binary operator
```

```
isEvenNumber <- function(n) {  
  if (! is.numeric(n)) { return(FALSE) }  
  return((n %% 2) == 0)  
}
```

```
isEvenNumber(2)
```

```
#> [1] TRUE
```

```
isEvenNumber("not_a_number")
```

```
#> [1] FALSE
```

Loops

Use `for` loops when the number of iterations is ***known***.

1. Build the sequence
2. Iterate over it

```
for (i in 1:5) { # Define the sequence
  cat(i, '\n')
}
```

```
#> 1
#> 2
#> 3
#> 4
#> 5
```

Use `while` loops when the number of iterations is ***unknown***.

1. Define stopping condition
2. Manually increase condition

```
i <- 1
while (i <= 5) { # Define stopping
  condition
  cat(i, '\n')
  i <- i + 1 # Increase condition
}
```

```
#> 1
#> 2
#> 3
#> 4
#> 5
```

Search for something in a sequence

Example: count the **even** numbers in sequence: 1, (2), 3, (4), 5

for loop

```
count <- 0 # Initialize count
for (i in seq(5)) {
  if (i %% 2 == 0) {
    count <- count + 1 # Update
  }
}
```

```
count
```

```
#> [1] 2
```

while loop

```
count <- 0 # Initialize count
i <- 1
while (i <= 5) {
  if (i %% 2 == 0) {
    count <- count + 1 # Update
  }
  i <- i + 1
}
```

```
count
```

```
#> [1] 2
```

Vectors

The universal vector generator: `c()`

Numeric vectors

```
x <- c(1, 2, 3)  
x
```

```
#> [1] 1 2 3
```

Character vectors

```
y <- c('a', 'b', 'c')  
y
```

```
#> [1] "a" "b" "c"
```

Logical vectors

```
z <- c(TRUE, FALSE, TRUE)  
z
```

```
#> [1] TRUE FALSE TRUE
```

Elements in vectors must be the same type

Type hierarchy:

- `character` > `numeric` > `logical`
- `double` > `integer`

Converts to characters:

```
c(1, "foo", TRUE)
```

```
#> [1] "1"    "foo"   "TRUE"
```

Converts to numbers:

```
c(7, TRUE, FALSE)
```

```
#> [1] 7 1 0
```

Converts to double:

```
c(1L, 2, pi)
```

```
#> [1] 1.000000 2.000000  
3.141593
```

Most functions operate on vector *elements*

```
x <- c(3.14, 7, 10, 15)
```

```
round(x)
```

```
#> [1] 3 7 10 15
```

```
isEven <- function(n) {  
  return((n %% 2) == 0)  
}
```

```
isEven(x)
```

```
#> [1] FALSE FALSE TRUE FALSE
```

"Summary" functions **return one value**

```
x <- c(3.14, 7, 10, 15)
```

```
length(x)
```

```
#> [1] 4
```

```
min(x)
```

```
#> [1] 3.14
```

```
sum(x)
```

```
max(x)
```

```
#> [1] 35.14
```

```
#> [1] 15
```

```
prod(x)
```

```
mean(x)
```

```
#> [1] 3297
```

```
#> [1] 8.785
```

Use brackets [] to get elements from a vector

```
x <- seq(1, 10)
```

Indices start at 1:

```
x[1] # Returns the first element
```

```
#> [1] 1
```

```
x[3] # Returns the third element
```

```
#> [1] 3
```

```
x[length(x)] # Returns the last element
```

```
#> [1] 10
```

Slicing with a vector of indices:

```
x[1:3] # Returns the first three  
elements
```

```
#> [1] 1 2 3
```

```
x[c(2, 7)] # Returns the 2nd and 7th  
elements
```

```
#> [1] 2 7
```

Use negative integers to *remove* elements

```
x <- seq(1, 10)
```

```
x[-1] # Drops the first element
```

```
#> [1] 2 3 4 5 6 7 8 9 10
```

```
x[-1:-3] # Drops the first three elements
```

```
#> [1] 4 5 6 7 8 9 10
```

```
x[-c(2, 7)] # Drops the 2nd and 7th elements
```

```
#> [1] 1 3 4 5 6 8 9 10
```

```
x[-length(x)] # Drops the last element
```

```
#> [1] 1 2 3 4 5 6 7 8 9
```

Slicing with logical indices

```
x <- seq(1, 20, 3)  
x
```

```
#> [1] 1 4 7 10 13 16 19
```

```
x > 10 # Create a logical vector based on some condition
```

```
#> [1] FALSE FALSE FALSE FALSE TRUE TRUE TRUE
```

Slice `x` with logical vector - only `TRUE` elements will be returned:

```
x[x > 10]
```

```
#> [1] 13 16 19
```

Comparing vectors

Check if 2 vectors are the same:

```
x <- c(1, 2, 3)  
y <- c(1, 2, 3)
```

```
x == y
```

```
#> [1] TRUE TRUE TRUE
```

Comparing vectors with `all()` and `any()`

`all()`: Check if *all* elements are the same

```
x <- c(1, 2, 3)
y <- c(1, 2, 3)
all(x == y)
```

```
#> [1] TRUE
```

```
x <- c(1, 2, 3)
y <- c(-1, 2, 3)
all(x == y)
```

```
#> [1] FALSE
```

`any()`: Check if *any* elements are the same

```
x <- c(1, 2, 3)
y <- c(1, 2, 3)
any(x == y)
```

```
#> [1] TRUE
```

```
x <- c(1, 2, 3)
y <- c(-1, 2, 3)
any(x == y)
```

```
#> [1] TRUE
```

Strings

Case conversion & substrings

Function	Description
<code>str_to_lower()</code>	converts string to lower case
<code>str_to_upper()</code>	converts string to upper case
<code>str_to_title()</code>	converts string to title case
<code>str_length()</code>	number of characters
<code>str_sub()</code>	extracts substrings
<code>str_locate()</code>	returns indices of substrings
<code>str_dup()</code>	duplicates characters

Quick practice:

05:00

Create this string object:

```
x <- 'thisIsGoodPractice'
```

Then use **stringr** functions to transform `x` into the following strings:

- `'thisIsGood'`
- `'practice'`
- `'GOOD'`
- `'thisthisthis'`
- `'GOODGOODGOOD'`

Hint: You'll need these:

- `str_to_lower()`
- `str_to_upper()`
- `str_locate()`
- `str_sub()`
- `str_dup()`

Padding, splitting, & merging

Function	Description
<code>str_trim()</code>	removes leading and trailing whitespace
<code>str_pad()</code>	pads a string
<code>paste()</code>	string concatenation
<code>str_split()</code>	split a string into a vector

05:00

Quick practice:

Create the following objects:

```
x <- 'this_is_good_practice'  
y <- c('hello', 'world')
```

Use `stringr` functions to transform `x` and `y` into the following:

- "hello world"
- "***hello world***"
- c("this", "is", "good", "practice")
- "this is good practice"
- "hello world, this is good practice"

Hint: You'll need these:

- `str_trim()`
- `str_pad()`
- `paste()`
- `str_split()`

Detecting & replacing

Function	Description
<code>str_sort()</code>	sort a string alphabetically
<code>str_order()</code>	get the order of a sorted string
<code>str_detect()</code>	match a string in another string
<code>str_replace()</code>	replace a string in another string

05:00

Quick practice:

```
fruit[1:5]
```

```
#> [1] "apple"        "apricot"       "avocado"      "banana"       "bell pepper"
```

Use `stringr` functions to answer the following questions about the `fruit` vector:

1. How many fruit have the string "`rr`" in it?
2. Which fruit end with string "`fruit`"?
3. Which fruit contain more than one "`o`" character?

Hint: You'll need to use `str_detect()` and `str_count()`

Begin list of all problems solved in class

General function writing

eggCartons(eggs): Write a function that reads in a non-negative number of eggs and prints the number of egg cartons required to hold that many eggs. Each egg carton holds one dozen eggs, and you cannot buy fractional egg cartons.

- `eggCartons(0) == 0`
- `eggCartons(1) == 1`
- `eggCartons(12) == 1`
- `eggCartons(25) == 3`

militaryTimeToStandardTime(n): Write a function that takes an integer between 0 and 23 (representing the hour in military time), and returns the same hour in standard time.

- `militaryTimeToStandardTime(0) == 12`
- `militaryTimeToStandardTime(3) == 3`
- `militaryTimeToStandardTime(12) == 12`
- `militaryTimeToStandardTime(13) == 1`
- `militaryTimeToStandardTime(23) == 11`

Number chopping

onesDigit(x): Write a function that takes an integer and returns its ones digit.

Tests:

- `onesDigit(123) == 3`
- `onesDigit(7890) == 0`
- `onesDigit(6) == 6`
- `onesDigit(-54) == 4`

tensDigit(x): Write a function that takes an integer and returns its tens digit.

Tests:

- `tensDigit(456) == 5`
- `tensDigit(23) == 2`
- `tensDigit(1) == 0`
- `tensDigit(-7890) == 9`

Top-down design

Create a function, `isRightTriangle(a, b, c)` that returns `TRUE` if the triangle formed by the lines of length `a`, `b`, and `c` is a right triangle and `FALSE` otherwise. Use the `hypotenuse(a, b)` function in your solution. **Hint:** you may not know which value (`a`, `b`, or `c`) is the hypotenuse.

```
hypotenuse <- function(a, b) {  
  return(sqrt(sumOfSquares(a, b)))  
}
```

```
sumOfSquares <- function(a, b) {  
  return(a^2 + b^2)  
}
```

Conditionals (if / else)

`getType(x)`: Write the function `getType(x)` that returns the type of the data (either `integer`, `double`, `character`, or `logical`). Basically, it does the same thing as the `typeof()` function (but you can't use `typeof()` in your solution).

- `getType(3) == "double"`
- `getType(3L) == "integer"`
- `getType("foo") == "character"`
- `getType(TRUE) == "logical"`

Conditionals (if / else)

For each of the following functions, start by writing a test function that tests the function for a variety of values of inputs. Consider cases that you might not expect!

isFactor(f, n): Write the function **isFactor(f, n)** that takes two integer values and returns **TRUE** if **f** is a factor of **n**, and **FALSE** otherwise. Note that every integer is a factor of **0**. Assume **f** and **n** will only be numeric values, e.g. **2** is a factor of **6**.

isMultiple(m, n): Write the function **isMultiple(m, n)** that takes two integer values and returns **TRUE** if **m** is a multiple of **n** and **FALSE** otherwise. Note that **0** is a multiple of every integer other than itself. Hint: You may want to use the **isFactor(f, n)** function you just wrote above. Assume **m** and **n** will only be numeric values.

Conditionals (if / else)

Write the function `getInRange(x, bound1, bound2)` which takes 3 numeric values: `x`, `bound1`, and `bound2` (`bound1` is not necessarily less than `bound2`). If `x` is between the two bounds, just return `x`, but if `x` is less than the lower bound, return the lower bound, or if `x` is greater than the upper bound, return the upper bound. For example:

- `getInRange(1, 3, 5)` returns `3` (the lower bound, since 1 is below [3,5])
- `getInRange(4, 3, 5)` returns `4` (the original value, since 4 is between [3,5])
- `getInRange(6, 3, 5)` returns `5` (the upper bound, since 6 is above [3,5])
- `getInRange(6, 5, 3)` returns `5` (the upper bound, since 6 is above [3,5])

Bonus: Re-write `getInRange(x, bound1, bound2)` without using conditionals

for loops

`sumFromMToN(m, n)`: Write a function that sums the total of the integers between `m` and `n`.

Challenge: Try solving this without a loop!

- `sumFromMToN(5, 10) == (5 + 6 + 7 + 8 + 9 + 10)`
- `sumFromMToN(1, 1) == 1`

`sumEveryKthFromMToN(m, n, k)`: Write a function to sum every `k`th integer from `m` to `n`.

- `sumEveryKthFromMToN(1, 10, 2) == (1 + 3 + 5 + 7 + 9)`
- `sumEveryKthFromMToN(5, 20, 7) == (5 + 12 + 19)`
- `sumEveryKthFromMToN(0, 0, 1) == 0`

`sumOfOddsFromMToN(m, n)`: Write a function that sums every *odd* integer between `m` and `n`.

- `sumOfOddsFromMToN(4, 10) == (5 + 7 + 9)`
- `sumOfOddsFromMToN(5, 9) == (5 + 7 + 9)`

for loop with break & next

`sumOfOddsFromMToNMax(m, n, max)`: Write a function that sums every *odd* integer from `m` to `n` until the sum is less than the value `max`. Your solution should use both `break` and `next` statements.

- `sumOfOddsFromMToNMax(1, 5, 4) == (1 + 3)`
- `sumOfOddsFromMToNMax(1, 5, 3) == (1)`
- `sumOfOddsFromMToNMax(1, 5, 10) == (1 + 3 + 5)`

while loops

isMultipleOf4Or7(n): Write a function that returns **TRUE** if **n** is a multiple of 4 or 7 and **FALSE** otherwise.

- `isMultipleOf4Or7(0) == FALSE`
- `isMultipleOf4Or7(1) == FALSE`
- `isMultipleOf4Or7(4) == TRUE`
- `isMultipleOf4Or7(7) == TRUE`
- `isMultipleOf4Or7(28) == TRUE`

nthMultipleOf4Or7(n): Write a function that returns the nth positive integer that is a multiple of either 4 or 7.

- `nthMultipleOf4Or7(1) == 4`
- `nthMultipleOf4Or7(2) == 7`
- `nthMultipleOf4Or7(3) == 8`
- `nthMultipleOf4Or7(4) == 12`
- `nthMultipleOf4Or7(5) == 14`
- `nthMultipleOf4Or7(6) == 16`

Loops / Vectors

isPrime(n): Write a function that takes a non-negative integer, **n**, and returns **TRUE** if it is a prime number and **FALSE** otherwise. Use a loop or vector:

- **isPrime(1) == FALSE**
- **isPrime(2) == TRUE**
- **isPrime(7) == TRUE**
- **isPrime(13) == TRUE**
- **isPrime(14) == FALSE**

nthPrime(n): Write a function that takes a non-negative integer, **n**, and returns the nth prime number, where **nthPrime(1)** returns the first prime number (2). Hint: use a while loop!

- **nthPrime(1) == 2**
- **nthPrime(2) == 3**
- **nthPrime(3) == 5**
- **nthPrime(4) == 7**
- **nthPrime(7) == 17**

Vectors

`reverse(x)`: Write a function that returns the vector in reverse order. You cannot use the `rev()` function.

- `all(reverseVector(c(5, 1, 3)) == c(3, 1, 5))`
- `all(reverseVector(c('a', 'b', 'c')) == c('c', 'b', 'a'))`
- `all(reverseVector(c(FALSE, TRUE, TRUE)) == c(TRUE, TRUE, FALSE))`

`alternatingSum(a)`: Write a function that takes a vector of numbers `a` and returns the alternating sum, where the sign alternates from positive to negative or vice versa.

- `alternatingSum(c(5,3,8,4)) == (5 - 3 + 8 - 4)`
- `alternatingSum(c(1,2,3)) == (1 - 2 + 3)`
- `alternatingSum(c(0,0,0)) == 0`
- `alternatingSum(c(-7,5,3)) == (-7 - 5 + 3)`

Strings

- 1) `reverseString(s)`: Write a function that returns the string `s` in reverse order.
 - `reverseString("aWordWithCaps") == "spaChtiWdrowA"`
 - `reverseString("abcde") == "edcba"`
 - `reverseString("") == ""`
- 2) `isPalindrome(s)`: Write a function that returns `TRUE` if the string `s` is a Palindrome and `FALSE` otherwise.
 - `isPalindrome("abcba") == TRUE`
 - `isPalindrome("abcb") == FALSE`
 - `isPalindrome("321123") == TRUE`

Strings

1) **sortString(s)**: Write the function `sortString(s)` that takes a string `s` and returns back an alphabetically sorted string.

- `sortString("cba") == "abc"`
- `sortString("abedhg") == "abdegh"`
- `sortString("AbacBc") == "aAbBcc"`

2) **areAnagrams(s1, s2)**: Write the function `areAnagrams(s1, s2)` that takes two strings, `s1` and `s2`, and returns `TRUE` if the strings are anagrams, and `FALSE` otherwise. **Treat lower and upper case as the same letters.**

- `areAnagrams("", "") == TRUE`
- `areAnagrams("aabbccdd", "bbccdde") == FALSE`
- `areAnagrams("TomMarvoloRiddle", "IAmLordVoldemort") == TRUE`